



MAKING IT EASIER TO CONTROL DC MOTORS

DC Digital Drive Feature comparison guide

SPRINT ELECTRIC

www.sprint-electric.com

This guide will show you the features of the PL/PLX range of DC drives when compared to its immediate competition. It is by no means an exhaustive comparison.

KEY ✓ = yes ✗ = no 🖱 = reduced specification £ = extra cost option

	PL/PLX	Parker SSD 590 +	CT Mentor2	Lenze 48/4900	ABB DCS500
Unique electronic regenerative stopping facility on most 2Q models.	✓	✗	✗	✗	✗
Plain language display for programmable connection points.	✓	✗	✗	🖱	✗
Digital I/P's and O/P's are short circuit proof.	✓	✗	✗	✗	🖱
Digital I/P's and O/P's are over-voltage protected.	✓	✗	✓	✗	✗
Main & Auxiliary power ports for quick current release at start.	✓	✗	✗	✓	✗
4 ergonomically designed keys for Up, Down, Left and Right for easy menu navigation.	✓	✗	✗	✗	✗
Motor drive alarms latched for display after power on / off, i.e. message not lost when power turned off.	✓	✗	🖱	✗	✗
Unique 'configuration checker' detects shorting of user programmed block diagram outputs.	✓	✗	✗	✗	✗
All analogue I/P's have a programmable voltage range up to +/- 30V with up to 5mv resolution with excellent response time.	✓	✗	🖱	🖱	🖱
All analogue I/P's are over-voltage protected.	✓	✗	✓	✗	✗
Ability to select 2 sets of motor parameters.	✓	✗	£	✗	✓
Windows based on/off line graphical configuration & diagnostic tool (supplied FOC inc. connection lead).	✓	✗	🖱	✗	£
Friendly easy to use menu structure with plain language parameter names.	✓	🖱	✗	✗	✗
Extensive programmable I/O.	✓	🖱	£	£	£
Significant panel space savings due to compact design.	✓	🖱	🖱	✗	✗
In depth diagnostic functionality available from on board display (in-built meter).	✓	🖱	🖱	🖱	✓
Built in oscilloscope output looking at ALL display parameters.	✓	🖱	✗	✗	£

KEY ✓ = yes ✗ = no 🖱 = reduced specification £ = extra cost option

	PL/PLX	Parker SSD 590 +	CT Mentor2	Lenze 48/4900	ABB DCS500
Ability to store 3 entire drive recipes.	✓	✗	£	✓	✗
Uniform product width across whole range.	✓	✗	✗	✗	✓
Up to 8 preset speeds by 3 inputs (with priority select).	✓	✗	🖱	🖱	🖱
Large Backlit 40 Character Alphanumeric LCD Display.	✓	🖱	✗	✗	✓
All feedback options as standard (Tacho, Encoder etc).	✓	£	✓	✓	✓
16 Motor drive alarms - displayed in plain language.	✓	✓	🖱	🖱	✓
Real language parameter description & pin number on display.	✓	🖱	✗	✓	✓
Self test message displays.	✓	✓	✗	✗	✓
Self ranging input for main stack supply 12V to 480V.	✓	✗	✓	✗	✗
Self ranging input for auxiliary supplies 100V to 480V.	✓	🖱	✗	✗	✗
Self ranging input for control supply 100V to 240V.	✓	🖱	✗	✗	🖱
In depth fault monitoring and comprehensive system alarms.	✓	✓	✓	✓	✓
Fully digital control loops.	✓	✓	✓	✓	✓
Control circuits fully isolated from power circuit.	✓	✓	✓	✓	✓
Choice of 2 adaptive armature current loop modes (Standard or Superfast).	✓	✗	✗	✗	✗
Self tuning current loop utilising "Autotune" algorithm.	✓	✓	✓	✓	✓
Steady state accuracy of 0.01% using encoder with digital reference. NB. No extra hardware required.	✓	£	£	✓	✓
Adjustable speed PI with integral defeat.	✓	✓	✓	✓	✓
All analogue O/P's short circuit protected.	✓	✓	✓	✓	✓
Drive to drive Total Recipe Exchange via serial link.	✓	✓	✓	✓	£
Drive to host Total Recipe Exchange via serial link.	✓	✓	✓	✓	£
Multiple drive 'daisy chain' data exchange facility via serial link (ideal for digital speed ratioing using encoder feedback. NB. No extra hardware needed).	✓	£	£	✓	£
Regeneration up to 1.2 x mains supply.	✓	✓	🖱	✗	✓
Field current programmable from minimum to 100% continuous with fail alarm.	✓	✓	✓	✓	✓



STANDARD SOFTWARE FUNCTIONS

With an extensive range of standard software blocks, the PL/X can easily take control of the most demanding motion tasks.

KEY ✓ = yes ✗ = no 🤖 = reduced specification £ = extra cost option

	PL/PLX	Parker SSD 590 +	CT Mentor2	Lenze 48/4900	ABB DCS500
Full suite of centre winding macro's	✓	✓	£	£	✗
Motorised Pot simulator with memory	✓	🤖	🤖	🤖	✗
2 x PID's (undedicated)	✓	🤖	£	🤖	✗
2 x Summers (undedicated)	✓	🤖	✓	🤖	✗
2 x Filters (undedicated)	✓	🤖	£	✗	✗
Dual Motor Swap	✓	✗	£	£	✓
Batch Counter	✓	✗	✗	✗	✓
Spindle Orientation	✓	✗	£	✓	✗
Latch	✓	✗	✗	✗	✗
Delay Timer	✓	✗	✗	✗	✗
Linear or S ramp	✓	✓	£	✓	✓
Current Profiling v Speed	✓	✓	✓	✓	✓
Jog / Crawl functions	✓	✓	✓	✓	✓
Slack take up	✓	✓	£	✓	✓
Draw control	✓	✓	✓	✓	✓
Auto Self-tune current loop	✓	✓	✓	✓	✓
8 independent Multi-function blocks	✓	🤖	🤖	🤖	🤖
4 independent Comparators	✓	✗	£	🤖	✗
4 independent Change-Over switches	✓	✗	£	✗	✗
16 Jumpers for interconnection of parameters	✓	🤖	🤖	✗	✓
Versatile Preset Value Selector	✓	✗	£	✗	✓
Parameter Profiler	✓	✗	£	✗	✗
3 User programmable complete drive recipe pages	✓	✗	✗	✓	✗
Copy & paste facility between all recipe pages	✓	✗	✗	✓	✗
'Overwrite lock out' facility on one recipe page	✓	✗	✗	✗	✗




INPUTS / OUTPUTS

Numerous inputs and outputs allow you to control a wider range of industrial applications without the need for external equipment.

KEY ✓ = yes ✗ = no 🖱 = reduced specification £ = extra cost option

	PL/PLX	Parker SSD 590 +	CT Mentor2	Lenze 48/4900	ABB DCS500
Analogue inputs					
8 (all programmable) (can also be utilised as digital i/p's)	8	5	5	4	5
Analogue outputs					
4 (3 programmable)	4	3	4	3	2
Digital inputs					
17 (all programmable)	17	9	9	5	8
Digital outputs					
7 (all programmable)	7	3	7	4	7
Speed feedback					
Analogue tacho	✓	£	✓	✓	✓
Encoder	✓	£	✓	✓	✓
Armature voltage	✓	✓	✓	✓	✓
Encoder + Armature volts or Analogue Tacho	✓	£	✓	✓	✗



PROTECTION

Reducing your downtime and maintenance costs by giving your DC motors added levels of protection.

KEY ✓ = yes ✗ = no 🖱 = reduced specification £ = extra cost option

	PL/PLX	Parker SSD 590 +	CT Mentor2	Lenze 48/4900	ABB DCS500
Interline device networks (snubber)	✓	✓	✓	✗	✓
High energy MOV's	✓	✓	✓	✓	✓
Overcurrent (instantaneous)	✓	✓	✓	✓	✓
Overcurrent (150% for 25s inverse time)	✓	✓	✓	🖱	✓
Field Failure	✓	✓	✓	✓	✓
Field Overcurrent	✓	✓	✓	✓	✓
Tacho and/or Encoder failure with auto AVF backup	✓	✗	✗	✓	✗
Motor over-temperature	✓	✓	✓	✓	✓
Thyristor Stack over-temperature	✓	✓	✓	✓	✓
Thyristor "Trigger" failure	✓	✓	✓	✓	✓
Zero speed detection	✓	✓	✓	✓	✓

Standstill logic	✓	✓	✓	✓	✓
Stall protection	✓	✓	✓	✓	✓
Digital Output short circuit Trip Alarm	✓	✗	✗	✗	✗
Overspeed	✓	✓	✓	✓	✓
Armature Overvolts	✓	✓	✓	✓	✓
Mains synchronisation loss	✓	✓	✓	✓	✓
Mains supply phase loss	✓	✓	✓	✓	✓
Digital Output limit 350mA	✓	👎	👎	👎	👎
Low leakage current	✓	👎	👎	👎	👎



FIELD CONTROL On board fully controlled field supply.

8A (12-123A ratings)

32A (430-630A ratings)

Optional 50A (430-1050A ratings)

Optional 100A (1250-2250A ratings)

16A (155-330A ratings)

32A (650-1050A ratings)

64A (1250-2250A ratings)

The field and armature supplies are input through separate terminals and may be at different levels if desired.

KEY ✓ = yes ✗ = no 👎 = reduced specification £ = extra cost option

	PL/PLX	Parker SSD 590 +	CT Mentor2	Lenze 48/4900	ABB DCS500
Fixed Voltage	✓	✓	✓	✓	£
Fixed Current	✓	✓	✓	✓	£
Field Economy	✓	✓	✓	✓	£
Field Weakening	✓	✓	£	✓	£
Delayed Quenching (for Dynamic Braking)	✓	✓	✓	✓	£
Standby field value (for keeping motor warm/no condensation)	✓	✓	✓	✓	£

PL PILOT CONFIGURATION & MONITORING SOFTWARE

The most powerful digital DC drive on the market needs the most flexible and robust software available.

The PL Pilot simplifies drive programming

- Easy to use 'Windows' based software
- Allows online and offline configuration
- Allows real time diagnostics and monitoring

This graphical diagnostic tool is included with every PL/X free of charge. PL Pilot makes interconnecting the drive's application blocks a simple task, and allows the user to tailor the drive's control strategy to meet the demands of the process or application exactly.

Sprint Electric, Peregrine House, Ford Lane, Ford, Arundel, West Sussex, BN18 0DF United Kingdom

Tel: +44 (0) 1243 558080 Fax: +44 (0) 1243 558099 Email: info@sprint-electric.com Web: www.sprint-electric.com